

**IN THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (currently amended) A transport ~~Transport~~ pipe for high viscosity materials, in particular for concrete, with comprising:

an inner pipe (10) made of an abrasion-resistant plastic,

at least one joint element (12) materially joined to an external end of the inner pipe (10), which includes a radially extending collar (16) and a ring sleeve concentric to the inner pipe (10) extending axially from one side thereof,

~~as well as~~ a reinforcing jacket (14) enclosing at least the internal pipe and connected thereto and to the joint element (12), ~~thereby characterized, that~~

wherein the radially projecting collar (16) of the joint element (12) is defined by a ring shaped end face (20) and by a thereto joined ring step (22) extending radially towards the inside of the pipe and recessed axially from the ring-shaped end face (22), and ~~that~~

wherein the plastic material of the inner pipe (10) engages from the inside of the pipe in the ring step (22).

2. (currently amended) The transport ~~Transport~~ pipe according to Claim 1, ~~thereby characterized, that~~ wherein the plastic

material of the inner pipe (10) fills the free area (24) bordered by the ring step (22) of the collar and thereby forms an on the end face (20) of the collar (16), radially inward, an end face part (26) preferably aligned or joining flush.

3. (currently amended) The transport ~~Transport~~ pipe according to Claim 1 ~~or 2~~, ~~thereby characterized, that~~ wherein extending from the recessed border surface of the ring step (22) a diagonal or curved transition surface (28) extends in the axial direction to the inner radius of the inside of the cylindrical ring sleeve (18).
4. (currently amended) The transport ~~Transport~~ pipe according to Claim 1 ~~one of Claims 1 through 3~~, ~~thereby characterized, that~~ wherein the inner surface of the cylindrical inner pipe (10) exhibits an opening which is slanted or curved diverging towards the end face (20, 26) of the collar (16).
5. (currently amended) The transport ~~Transport~~ pipe according to Claim 1 ~~one of Claims 1 through 4~~, ~~thereby characterized, that~~ wherein the reinforcing jacket (14) is a steel pipe, on the ends of which the ring sleeve (18) of the, preferably truncated, joint element (12) is welded.

6. (currently amended) The transport ~~Transport~~ pipe according to Claim 5, ~~thereby characterized, that wherein~~ the inner pipe (10) is a wear resistant inner coating for the steel pipe (14) and the attached joint element (12).
  
7. (currently amended) The transport ~~Transport~~ pipe according to Claim 1 ~~one of Claims 1 through 4, thereby characterized, that wherein~~ the ring sleeve (18) of the joint element exhibits an outer surface (34) with outer diameter varying in the axial direction, and that the reinforcing jacket (14) is formed by a fiber structure impregnated in a plastic matrix and tightly cohesively wound externally on the inner pipe (10) and the ring sleeve (18) of the joint element (12), which reinforcing jacket (14) is connected with the outer surface (34) of the ring sleeve (18) form-fittingly and in certain cases materially joined.
  
8. (currently amended) A transport ~~Transport~~ pipe for high viscosity materials, in particular for concrete, with comprising:
  - an inner pipe (10) made of an abrasion-resistant plastic,
  - at least one joint element (12) materially joined to an external end of the inner pipe (10), which includes a radially extending collar (16) and a ring sleeve concentric

to the inner pipe (10) extending axially from one side thereof, as well as

a reinforcing jacket (14) which envelops at least the internal pipe and is connected thereto and to the joint element (12),

~~thereby characterized, that~~ wherein the ring sleeve (18) of the joint element exhibits an outer surface (34) with outer diameter varying in the axial direction, and ~~that~~

wherein the reinforcing jacket (14) is formed by a fiber structure impregnated in a plastic matrix and tightly cohesively wound externally on the inner pipe (10) and the ring sleeve (18) of the joint element (12), which reinforcing jacket (14) is connected with the outer surface (34) of the ring sleeve (18) form-fittingly and in certain cases materially joined.

9. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~or 8~~, ~~thereby characterized, that~~ wherein the fiber structure is fiber cable or thread, fiber tape, fabric tape or mat.
10. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 9~~, ~~thereby characterized, that~~ wherein the fiber structure contains fiber material from the group consisting of carbon fiber, glass fiber, aramide fiber and/or polyester fiber.

11. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 10~~, thereby ~~characterized, that~~ wherein the fiber structure includes fiber layers laid axially and/or radially.
12. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 11~~, thereby ~~characterized, that~~ wherein the ring sleeve (18) exhibits a wave shape running in the axial direction.
13. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 11~~, thereby ~~characterized, that~~ wherein the ring sleeve (18) exhibits a shape which in the axial direction is trapezoid shaped, step shaped, grooved or knurled.
14. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 13~~, thereby ~~characterized, that~~ wherein the joint element (12) is provided with pins, about which the fiber structure is laid forming loops.
15. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 14~~, thereby ~~characterized, that~~ wherein the reinforcing jacket (14) and the joint element (12) are bolted together.

16. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 15~~, thereby ~~characterized, that~~ wherein on the two ends of the inner pipe (10) respectively one joint element (12) is provided, the joint element (12) including a ring sleeve (18) which on the outer surface is waved shaped.
17. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 15~~, thereby ~~characterized, that~~ wherein only on one, preferably the entry side, end of the inner pipe (10) a joint element (12) with ring sleeve (18) waved on the outside is provided, while on the other, preferably the exit, end a joint element (44) with external flat ring sleeve (46) is adhered.
18. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 17~~, thereby ~~characterized, that~~ wherein the ring sleeve (18) of the joint element (12) becomes tapered on its free end opposite to the collar (16).
19. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 18~~, thereby ~~characterized, that~~ wherein the wave contour of the outer

surface of the ring sleeve (18), towards its free end, becomes more shallow.

20. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 19~~, thereby ~~characterized, that~~ wherein the wave contour on the outer surface exhibits, immediately adjacent the collar (16), an axially joining, sharp edged radial rebounding wave valley (40).
21. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 20~~, thereby ~~characterized, that~~ wherein between the wave valley (40) closest to collar and the free end of the ring sleeve (18) at least two wave peaks (38) appear separated from each other by at least one further wave valley (42).
22. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claim 7 through 21~~, thereby ~~characterized, that~~ wherein the sequential wave peaks (38) exhibit a decreasing radial height going towards the free end of the ring sleeve (18).
23. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 1 through 22~~, thereby ~~characterized, that~~ wherein the inner pipe (10) is comprised of wear resistant polyurethane.

24. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 1 through 23~~, thereby ~~characterized, that~~ wherein the inner pipe (10) is cast on to the joint element (12), preferably via an adhesion promoter or primer applied over the joint element.
25. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 24~~, thereby ~~characterized, that~~ wherein the fiber structure embedded in the plastic matrix is materially joined with the inner pipe (10) with the formation of a closed reinforcing jacket (14).
26. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 7 through 25~~, thereby ~~characterized, that~~ wherein for the plastic matrix a plastic material is selected from the group consisting of epoxy resin, polyester resin, vinyl resin, and thermal plastic resin.
27. (currently amended) The transport ~~Transport~~ pipe according to Claim 1 ~~one of Claims 1 through 26~~, thereby ~~characterized, that~~ wherein the joint element (12) is metal, preferably steel.



28. (currently amended) The transport ~~Transport~~ pipe according to Claim 7 ~~one of Claims 1 through 26~~, thereby ~~characterized, that~~ wherein the joint element (12) is comprised of a plastic molded part reinforced with fiber, preferably injection molded or produced in a press mold.
29. (currently amended) A process ~~Process~~ for producing a transport pipe for viscous material, in particular for concrete, with the following process steps:
- introducing at least one premanufactured metallic joint part provided with a collar (16) and an externally wave shaped ring sleeve (18) ~~is introduced~~ on one end of a casting mold which is then cast with a reaction plastic which is wear resistant in the cured state with formation of an inner pipe with a collar at one end;
  - winding about the finished internal pipe with collar or flange ~~is wound about~~ with a plastic impregnated carbon fiber from one end to the other with the formation of the externally wave shaped ring liner and formation of a cohesive reinforcing jacket;
  - heating the finished transport pipe ~~is heated~~ for a period as necessary for curing of the plastic matrix and/or for production of a form-fitting joint with the inner pipe and the joint element (12).

30. (currently amended) The process ~~Process~~ according to Claim 29, ~~thereby characterized, that~~ wherein the joint element (12) is coated with an adhesion promoter or primer on its contact surfaces with the inner pipe (10) prior to the casting process.
31. (currently amended) The process ~~Process~~ according to one of Claims 29 ~~or 30~~, ~~thereby characterized, that~~ wherein the inner pipe and/or the joint element is coated with an adhesion promoter or primer on its surfaces contacting with the casing pipe prior to the wrapping process.
32. (currently amended) The process ~~Process~~ according to Claim 29 ~~one of Claims 29 through 31~~, ~~thereby characterized, that~~ wherein as the plastic matrix a plastic from the group epoxy resin, polyester resin, and vinyl resin, thermoplastic is employed.
33. (currently amended) The process ~~Process~~ according to Claim 29 ~~one of Claims 29 through 32~~, ~~thereby characterized, that~~ wherein the fiber cord or thread or the fabric tape is wound by means of a multi-axis winding machine with rotation of the inner pipe about its axis.
34. (currently amended) The process ~~Process~~ according to Claim 33, ~~thereby characterized, that~~ wherein the inner pipe with

collar is seated fixed against rotation upon a winding core, and that the winding core is rotated about the axis of the inner pipe by a motor during the winding process.

35. (currently amended) A process ~~Process~~ for producing a transport pipe for viscous matter, in particular concrete, with the following process steps:

- winding about at least one premanufactured joint element (12) including a collar (16) and a ring sleeve (18), the ring sleeve (18) wave shaped on the outside, ~~is wound about~~ with a plastic impregnated carbon fiber cord to form a carbon fiber composite pipe;

- then cleansing the produced carbon fiber composite pipe ~~is cleansed~~ on the inside and cleansing the joint element ~~is cleansed~~ on its free contact surfaces and coating coated with an adhesion promoter;

- subsequently introducing a reaction plastic ~~is introduced~~ into the carbon fiber composite pipe with its at least one collar, forming an inner coating, and curing as such ~~is cured~~.

36. (currently amended) The process ~~Process~~ according to Claim 35, ~~thereby characterized, that~~ wherein after the coating with the adhesion promoter a core with smaller dimension is

introduced into the inside of the carbon fiber composite pipe provided with at least one collar (16), with maintaining free a ring gap, and that subsequently the reaction plastic is introduced into the ring gap, is cured there, and the core is again removed.

37. (currently amended) The process ~~Process~~ according to Claim 36, ~~thereby characterized, that~~ wherein the reaction plastic is sprayed or spun on the inner surface of the carbon fiber composite pipe provided with at least one collar and coated with the adhesion promoter, and that the reaction plastic is subsequently cured.
38. (currently amended) A method for transporting concrete, comprising transporting concrete through the mobile or stationary concrete pump of Claim 1 ~~Use of the transport pipe according to one of Claims 1 through 19 for employment in conjunction with mobile or stationary concrete pumps.~~
39. (currently amended) A method for transporting concrete, comprising transporting concrete through the concrete distribution boom in mobile or stationary concrete pumps of Claim 1 ~~Use of the transport pipe according to one of Claims 1 through 19 for employment in.~~